

A.S.P. Electro-Technology Ltd


Tel: +44 (0) 1455 635796
Fax: +44 (0) 1455 610851

sales@asp-electro-tech.com
www.asp-electro-tech.com

6 Series EEx de 610 Beacon / Warning Light



Xenon Flash with Fresnel



LED cluster



Terminal block housing

Certification and Approval


- **Certification Code**
EEx de II 2 GD IIC T3 and 4
(See lamp tables for T rating)
- **Certification number**
SIRA 00 ATEX 1048
- **Certification standard**
EN 60079-0, 1, 7
- **Protection IP 66**

Features


- Rotating Beacon
- Xenon flashing unit
- IIC as standard
- Heavy Duty construction
- Integral EEx e terminal chamber
- FOR AMBIENT TEMPERATURE "T" RATINGS SEE TABLES AT REAR OF CATALOGUE

Options

- Range of fresnel colours or glass colouring
- Long Life LED options
- Range of warning and flash options
- High ambient version



Optional Pivot Bracket



Technical Data

Supply Voltage	Beacons 240v Warning Lights AC – 24 to 277 50/60Hz DC also
Operating Temperature	-45°C to +70°C
Control Gear (when Fitted)	<ul style="list-style-type: none"> • Electronic flasher unit • Rotating Reflector drive
Lamp Options	Beacons: 150w GLS max (ES, E27 or BC) 25w SL (ES, E27 or BC), 20w PLCE Rotating 55w of 70w (supplied)
Cable Entries	2 x M20 – ISO (1 plugged) as Standard Other threads available.
Terminals	<ul style="list-style-type: none"> • 4 (4mm) wire and earth with looping facility • Cable crimping required at installation when looping
Mounting Facility	Back mounted fixing strap
Access	<ul style="list-style-type: none"> • Terminals accessed via terminal cover retained by cap screws • Lamp and gear accessed via removable glass dome
Material	<ul style="list-style-type: none"> • Corrosion resistant marine grade aluminium body and bezel • Toughened Borosilicate glass dome
Finish	<ul style="list-style-type: none"> • 2 Pack epoxy paint on primed surface. • Standard colour - Aqua • Additional costs for non standard colours
Accessories	<ul style="list-style-type: none"> • Internal or external reflector • Pivot bracket for directional control • Pendant mount • Wire Guard • Glass colouring available
Weight	9.0Kgs
Features	<ul style="list-style-type: none"> • Flashing Xenon – Output 195,000CD peak OR Rotating Reflector beacon. • 70°C ambient option available • IIC as standard • Heavy Duty Construction