

Solid Front Safety Pattern Pressure Gauge **GS Range**

- Nominal Diameter options of 100mm, 150mm St.St. case
- Nominal Diameter 125mm Phenolic case
- Degree of Protection IP55/IP65.
- Blowout Protection.
- Ranges up to 4000bar
- Monel pressure connection, material and options available.
- ATEX II 2 G/D option

Performance **characteristics**

Enclosure options

- IP55 Protection for non filled
- IP65 Protection for filled

Pressure Connection Material

- 316 Stainless Steel as standard

Dials

- White Aluminium with black graduation

Process connection

- $\frac{1}{2}$ -14 NPT, G1/2B or 5/8"-18 UNF, M16 x 1.5 for high pressure applications

Accuracy

- Model GS 1.0 per EN 837-1:1998 , 0.6 optional

Ambient temperature

- -30 to +60 °C non fluid
- +10 to +60 °C glycerine filled
- -30 to +60 °C silicone fluid filled

Process temperature

- -30 to +250 °C non fluid
- +10 to +80 °C glycerine filled
- -30 to +120 °C silicone fluid filled
- +10 to +150 °C (ranges 2500/4000 bar)



Product **applications**

The **GS range** is suitable for a wide range of applications in many Industry sectors where a safety barrier & blow out back are required to give added safety:

- Oil & Gas
- Chemical
- Petrochemical
- Refining
- Power
- Marine
- Food Industry
- OEM

The choice of models available ensures suitability for use in:


- Corrosive atmospheres
- Resistant to chemical attack

How can we **help you?**

Delta Controls' range of reliable pressure and temperature measurement instruments can be customised to meet individual requirements. For technical advice or to discuss your application please contact us on +44 (0) 20 8939 3500

Model


TABLE 1



	Code
Industrial Service Pressure Gauge 100mm: -1 to 0 & 0 to 1600 Bar 150mm: -1 to 0 & 0 to 4000 Bar 125mm: -1 to 0 & 0 to 1000 Bar Refer to Table 2	GS
ATEX certified Industrial Service Pressure Gauge ATEX service pressure gauge - II 2 G/D other specification as GS	AS

Range

TABLE 2



	Range	Bar	Kg/cm ²	MPa	KPa	PSI	inHg & PSI	Code
Vacuum Gauge	-1 to 0	√	√					A0
	-100 to 0				√			AA
	-130 to 0						√	AB
Compound Ranges	-1 to + 0.6	√	√					CF
	-1 to + 1.5	√	√					G3
	-1 to +3	√	√					CG
	-1 to + 5	√	√					CH
	-1 to + 9	√	√					CI
	-1 to + 15	√	√					CJ
	-1 to + 24	√	√					CK
	-30 to +15						√	CL
	-30 to +30						√	CM
	-30 to +150						√	CN
	-100 to +150					√		GJ
	-100 to +300					√		CA
	-100 to +500					√		CD
	-100 to +900					√		CP
	-100 to +1500					√		CQ
	-100 to +2400					√		CR
Gauge Pressure Ranges	0 to 1	√	√					DA
	0 to 1.6	√	√					DB
	0 to 2.5	√	√					DC
	0 to 4	√	√					DD
	0 to 6	√	√	√				DE
	0 to 10	√	√	√				EA
	0 to 15					√		DK
	0 to 16	√	√	√				EB
	0 to 25	√	√	√				EC
	0 to 30					√		DP
	0 to 40	√	√	√				ED
	0 to 60	√	√	√		√		EE
	0 to 100	√	√	√	√	√		FA
	0 to 160	√	√	√	√	√		FB
	0 to 200					√		PF
	0 to 250	√	√	√	√			FC
	0 to 300					√		ER
	0 to 400	√	√	√	√	√		FD
	0 to 600	√	√		√	√		FE
	0 to 1000	√	√		√	√		GA
0 to 1500					√		F6	
0 to 1600	√	√		√			GB	
0 to 2000					√		UB	
0 to 2500	√	√		√			GC	

Range

Continued Table 2

	Range	Bar	Kg/cm ²	MPa	KPa	PSI	inHg & PSI	Code
Gauge Pressure Ranges	0 to 3000					√		UF
	0 to 4000	√	√		√	√		V2
	0 to 5000					√		W2
	0 to 6000					√		W9
	0 to 10000					√		YF
	0 to 15000					√		YK
	0 to 20000					√		YP

Pressure Units

TABLE 3

	Code
Kg/cm ²	B
Vacuum inches Hg and pressure PSI	C
Bar	H
MPa	I
KPa	J
psi	P

Inner Scale

TABLE 4

	Code
Inner Scale not required	0
Kg/cm ²	B
Vacuum inches Hg and pressure PSI	C
Bar	H
MPa	I
KPa	J
psi	P

Over Pressure

TABLE 5

	Code
130 percent of full scale deflection up to 1600 bar ranges	1
160 percent of full scale deflection up to 60 bar ranges	2
250 percent of full scale deflection up to 60 bar ranges	3
Equal to full scale deflection (2500/4000 bar)	0

Gauge Diameter

TABLE 6

	Code
100mm (nominal 4") St. St. case only	4
150mm (nominal 6") St. St. case only	6
125mm (nominal 5") phenolic case only	5

Material of Gauge Case


TABLE 12



	Code
Gauge nominal diameter 100 or 150mm diameter - Case and ring in AISI 304 stainless steel with laminated safety glass window	0
Gauge nominal diameter 100mm (4inch), case and ring with bayonet bezel in AISI 316 stainless steel with laminated safety glass window	1
Gauge nominal diameter 150mm (6inch), case and ring with bayonet bezel in AISI 316 stainless steel with laminated safety glass window	2
Gauge nominal diameter 125mm - Phenolic casing with methacrylate window	5
Gauge nominal diameter 125mm - Phenolic casing with laminated safety glass window	6

Scale Pointer Options

TABLE 13



	Code
Standard only no options this model	0
Elastic pointer stop in case of sudden return to zero	5

Options Available

TABLE 14



	Code
No additional options required	0
Tag number printed on dial face (Nominal gauge diameters 100mm (4inch) and 150mm (6inch) St. St. casing	1
Tag number printed on dial face (Nominal gauge diameter 125mm (4 1/2") Phenolic casing	2
Stainless steel tag plate.	4
Serial number printed on dial face (Nominal gauge diameters 100mm (4inch) and 150mm (6inch) St. St. casing	5
Serial number printed on dial face ((Nominal gauge diameter 125mm (4 1/2"inch) Phenolic casing	6

Treatments Available

TABLE 15



	Code
No additional treatment required	0
Tropicalised	1
Wetted parts prepared for Oxygen service.	4

In the interest of development and improvement Delta Controls Ltd, reserves the right to amend, without notice, details contained in this publication. No legal liability will be accepted by Delta Controls Ltd, for any errors, omissions or amendments.



Delta Controls Ltd

Island Farm Avenue, West Molesey, Surrey, KT8 2UZ, United Kingdom

T+44 (0) 208 939 3500 F+44 (0) 783 1163 E sales@delta-controls.com W www.delta-controls.com

